



Part No	90NR02Z1-M01430
Model Name	GX550LXS-HC071R
EAN Code	4718017742207
UPC Code	192876742204
Marketing Name	ROG Zephyrus Duo 15
Color	Gunmetal Gray
Dimension (W x D x H)	36.0 x 26.8 x 2.09 ~ 2.09 cm 14.17 x 10.56 x 0.82 ~ 0.82 inches
Weight	2.48 Kg 5.47 Lb
Processor	Intel® Core™ i9-10980HK Processor 2.4 GHZ (16M Cache, up to 5.3 GHZ)
Chipset	Mobile Intel® HM470 Express Chipsets
Discrete/Optimus	GPU Switch (Discrete/Optimus)
Graphic	NVIDIA® GeForce® RTX 2080 SUPER™ with Max-Q Design
Graphic Memory	8GB GDDR6
IGPU	Intel® UHD Graphics
Panel Size	15.6-inch
Resolution	4K UHD (3840 x 2160) 16:9
Refresh Rate	60Hz
Viewing Angle	85/85/85/85
Panel Tech	IPS-level
Brightness	400
Contrast	1200:1
NTSC %	95.54%
SRGB %	132.70%
Adobe %	100%
Anti glare	anti-glare display
Adaptive-Sync technology	G-Sync
Pantone Validated	Yes
Total System Memory	16GB DDR4 on board + 16GB DDR4-3200 SO-DIMM(for i7-10875H/i9-10980HK) 16GB DDR4-2933 SO-DIMM(for i5-10300H/i7-10750H)
On board memory	16GB DDR4 on board
Memory Slot	1x SO-DIMM slot
DIMM Memory	16GB DDR4-3200 SO-DIMM(for i7-10875H/i9-10980HK) 16GB DDR4-2933 SO-DIMM(for i5-10300H/i7-10750H)
Memory Max.	32GB
System Storage Installed	1TB + 1TB M.2 NVMe™ PCIe® 3.0 Performance RAID0 SSD
M.2 slots support either SATA and NVMe	2
M.2 SSD Support List	1. 2xPCIe*4 2. 512G / 1TB
On board Wireless	Intel Wi-Fi 6(Gig+)(802.11ax)+Bluetooth 5.1 (Dual band) 2*2 (*BT version may change with OS upgrades.) -RangeBoost

LAN	10/100/1000 Mbps
I/O Ports	2x USB 3.2 Gen 1 Type-A 1x USB 3.2 Gen 2 Type-A 1x Type C USB 3.2 Gen 2 with Power Delivery, Display Port, G-Sync and Thunderbolt™ 3 1x RJ45 LAN port//1x Headphone out. 1x MIC in
Thunderbolt	Thunderbolt™ 3
Display output	1x HDMI 2.0b
Webcam	Optional
Mic	Built-in array microphone
Keyboard Type	Backlit Chiclet Keyboard Per-Key RGB
NumberPad	NumberPad
Aura Sync	Yes
Speakers	2x 4W speaker with smart AMP technology
Audio Tech	ESS Smart Amp DAC
Operating System	Windows 10 Pro - ASUS recommends Windows 10 Pro for business
Office	1-month trial for new Microsoft 365 customers. Credit card required.
Security	BIOS Administrator Password and User Password Protection
Battery	90WHrs, 4S1P, 4-cell Li-ion
Power	ø6.0 240W AC Adaptor Output: 20V DC, 12A, 240W Input: 100~240C AC 50/60Hz universal
Bundled Peripherals	ROG ranger BP2500 backpack & marketing giveaway