

## HP DesignJet T850 36-in Multifunction Printer



2Y9H2A Series  $\rightarrow$ 

# **Specifications**

All Specs

Color(s) of printing supplies

Cyan, magenta, yellow, matte black

Connectivity, standard

Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n

Copy reduce / enlarge settings

50 to 400%

Electromagnetic compatibility

Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand

(RSM), China (CCC), Japan (VCCI); Korea (KCC)

End of Life CO2e (kg)

Energy star certified

Yes

**Environmental certification** 

ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable

WW RoHS materials restriction requirements.

Finished output handling

Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter

**Functions** 

Print, copy, scan

HP ePrint capability

Yes

Ink drop

6 pl (C, M, Y); 12.6 pl (mK)

Ink types

Pigment-based (C, M, Y, mK)

Internal Storage

None

Line accuracy

±0.1%[2]

Linear scan speed

Up to 3.81 cm/sec (color, 200 dpi), up to 11.43 cm/sec (grayscale, 200 dpi)

Manufacturer Warranty

Two-year limited hardware warranty. Warranty and support options vary by product, country and local legal requirements.

Maximum media thickness

Up to 0.8 mm

Maximum optical density (black)

15 L\* min/1.7 D[3]

Maximum scan length

7 m[4]

Media sizes standard (metric

rolls)

369 to 914 mm

Media sizes supported

Input tray: A4, A3; Manual feed: A4, A3, A2, A1, A0

Media sizes, custom

Input tray: 210 x 279 to 305 x 457 mm; Manual feed: 210 x 279 to 914 x 1676 mm

Media thickness

Up to 11.8 mil

Media thickness (metric)

Up to 0.3 mm

Media types

Bond and coated paper (bond, coated, heavyweight coated, plain, bright white, blueprint), technical paper (natural tracing), film (clear, matte), photographic paper (ID satin, ID gloss), self-adhesive (adhesive matte/gloss, adhesive polypropylene gloss),

Polypropylene (matte)



Media weight, recommended 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray)

Media width, maximum 914 mm

Memory 2 GB

Model size 914 mm

Network ready Standard

Non-Operating Humidity Range 0 to 95% RH

Non-printable area (cut-sheet)  $5 \times 5 \times 5 \times 5 \text{ mm}$ 

Non-printable area (roll media) 5 x 5 x 5 x 5 mm

Number of print cartridges 4 (C, M, Y, mK)

Operating altitude Up to 3000 m

Operating humidity range 20 to 80% RH

Operating temperature range 41 to 104°F

Orderable supplies HP Original Ink: HP 738 cartridges (Black, Cyan, Magenta, Yellow), and HP 739 printhead

Post consumer recycled plastic in hardware by weight of plastic

37%

Power Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max

 $\textbf{Power consumption} \hspace{1.5cm} 35 \text{ W (printing), } < 11 \text{ W (ready), } < 3.5 \text{ W (sleep), } < 0.1 \text{ W (standby). } \\ \text{Auto-scheduled printer on/off usage.} \\ \textbf{Solution of the printer on of the printer of the printer of t$ 

Print cartridge volume delivered 300 ml, 130 ml

Print head nozzles 1376 per color; 5504 in total

Print heads 1 (C, M, Y, mK)

Print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4

Print multi-size files in one click Yes

Print quality color (best)

Up to 2400 x 1200 optimized dpi

Print speed 25 sec/page on A1, 90 A1 prints per hour[1]

No

Print Technology Ink

Print technology HP Thermal Inkjet

Printer drivers included Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows

Wi-Fi Direct, remote printing, HP Click App, HP Click Driver for Windows 11, Apple AirPrint and HP app for Android and iOS devices,

Windows and mage OS printer drivers, printing support for Chroma OS, print from USP, pop drive

 $Windows\ and\ macOS\ printer\ drivers, printing\ support\ for\ Chrome\ OS, print\ from\ USB\ pen\ drive$ 

Product display name

HP DesignJet T850 Large Format 36-in Multifunction Plotter Printer with Automatic A1/D and A3/B Printing in One Device

Production CO2e (kg) 1152

Recommended media

HP Universal Bond Paper (FSC\* certified)[5] (recyclable)[6];HP Coated Paper (FSC\* certified)[5] (recyclable)[6];HP Heavyweight

Coated Paper (FSC® certified)[5] (recyclable)[6]

Registration required



Remote print enabled Yes

Roll external diameter 100 mm

Roll maximum input 1

Roll maximum weight 6.2 kg

Safety

USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina

(IRAM); India (BIS)

Scan file format JPEG, PDF, TIFF

Scan input modes Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP app.

Scan resolution, optical Up to 600 dpi

Scan size, maximum 914 mm x 2.77 m

Scan size, minimum 127 x 127 mm

Scanner type Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method

Security features

HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL,

NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration

Software included HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS

Storage temperature range -13 to 131°F

Supported Primary Applications Line drawings; Renderings; Presentations; Maps; Posters

Technical features

A3 input tray;1-click scan/copy;130/300 ml cartidges;Auto-power on/off scheduler;Max. resolution 2400 x 2400 dpi;Sheet organizer

accessories;HP Wolf Pro Security;HP Flex Tech Inks

Theoretical minimum line width 0.02 mm (via raster driver)

Total CO2e (kg)

Total CO2e (kg) note

A product carbon footprint is defined as the total amount of greenhouse gases emitted directly and indirectly by a product over its

lifetime. Greenhouse gas emissions are reported as global warming potential for 100-year time horizon (GWP-100) in units of CO2 equivalence. Calculations are done in accordance with ISO 14040 & ISO 14044. Individual values may not sum to total due to

rounding.

Transportation CO2e (kg) 104

UNSPSC code 43212104

What's in the box HP DesignJet T850 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord

Logistics

Minimum dimensions (W x D x H) 1407 x 701 x 967 mm


Package dimensions (W x D x H) 1575 x 570 x 650 mm

Package weight 83.5 kg

UNSPSC code 43212104

UPC number (AB1) 198701770657; (B19) 196548313228

Weight 60 kg



#### What's in the box

HP DesignJet T850 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord

### Specifications

[1] Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.

[2]  $\pm 0.1\%$  of the specified vector length or  $\pm 0.2$  mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.

[3] With HP Universal Instant Dry Photo Gloss media with Original HP inks.

[4] Scanned at 200 dpi using "Long Plot" setting.

[5] BMG trademark license code FSC\*-C115319, see http://www.fsc.org . HP trademark license code FSC\*-C017543, see http://www.fsc.org

[6] Can be recycled through commonly available recycling programs.

## Legal disclaimer

Product image may differ from actual product

AirPrint; CE marking; ENERGY STAR; EPEAT green; IPv6 Ready; Mac; Wi-Fi Certified; Windows 11 Compatible